

DECLARATION OF PERFORMANCE NO. 5/2016

1. Identification code of the product:		ACKERMAN P5	
2. Element allowing product identification:		Product name: ACKERMAN P5	
(type, batch, serial number)		Batch number: on the label	
3. Intended use of the product:		Solid fuel heater intended for heating residential premises	
4. Name and contact address		ACKERMAN S.A.	
of the manufacturer:		ul. Lektykarska 54, 01-687 Warszawa, Poland	
5. Name and contact address		Not applicable	
of the authorised representative:			
6. System or systems of assessment		System 3	
and verification of constancy of performance of the product:			
7. Name and identification number		Institut Nofty i Cozy. Paástyovy Institut Padayezy	
of the notified body and the number		Instytut Nafty i Gazu - Państwowy Instytut Badawczy, notified body no. 1450 performed the verification of performance	
of the test report:		of the product and issued test report no. 3398 A2 14	
8. DECLARED PERFORMANCE			
Essential characteristics:	Performance:		Harmonised technical specification:
Fire safety:			EN 13240:2001/A2:2004/AC:2007
- Safety distances to combustible materials	Minimal distance in mm:		EN 13240:2001/A2:2004/AC:2007
		nder the appliance = 0	
	Front, back, side, top = 1500		
		der the appliance should be non-combustible materials	
Hazards related to the loss of the firebed and escape of harmful combustion gases into the room	No hazards		EN 13240:2001/A2:2004/AC:2007
- Safety of fuel filling	Pass		EN 13240:2001/A2:2004/AC:2007
- Equipping the device with an adjustable and properly marked adjustment device	Pass		EN 13240:2001/A2:2004/AC:2007
- Keeping heating surfaces clean	Pass		EN 13240:2001/A2:2004/AC:2007
- Proper and efficient appliance operation	Pass		EN 13240:2001/A2:2004/AC:2007
Electrical safety	Not applicable		EN 13240:2001/A2:2004/AC:2007
Nominal heat output	7,5 kW		EN 13240:2001/A2:2004/AC:2007
Heating efficiency	80,3%		EN 13240:2001/A2:2004/AC:2007
CO emission in combustion products at 13% O ₂	0,098%		EN 13240:2001/A2:2004/AC:2007
Refuelling intervals	0,76 h		EN 13240:2001/A2:2004/AC:2007
Flue gas temperature at nominal heating power	290°C		EN 13240:2001/A2:2004/AC:2007
Surface temperature	Pass		EN 13240:2001/A2:2004/AC:2007
Durability	Pass		EN 13240:2001/A2:2004/AC:2007
Mechanical resistance	Pass		EN 13240:2001/A2:2004/AC:2007
(to carry a chimney/flue)	1, 4,33		2.1 232 10.2001/12.200 1/mc.2007
Release of dangerous substances	No rele substar	ase of dangerous nces	EN 13240:2001/A2:2004/AC:2007

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Updated: 01.02.2018

Signed for and on behalf of the manufacturer by:

Warsaw, June 2nd, 2016 Dariusz Matulka, CEO